

New HMT® Pro-Fill System automatically fills your hot melt tank and keeps it filled.

Boost the efficiency of your hot melt operation with our new Pro-Fill System. Compatible with all HMT® Hot Melt Systems, it draws bulk adhesive from any nearby container to replenish the melt tank automatically – without the need for labor-intensive manual loading.

The Advantages Are Many

- Keeps the melt tank full for steady, uninterrupted flow of hot melt
- Supplants manual loading; reduces labor and operator reliance
- Improves safety; minimizes worker contact with hot adhesives or surfaces
- Cuts adhesive waste, charring and downtime
- Prevents melt tank overflowing and spilling

System Operation Is Simple

- Place the hands-free, vacuum wand in boxes, large plastic canisters or shipping containers holding bulk hot melt pellets or slats
- A level sensor on the melt tank signals the vacuum wand when hot melt levels draw below a pre-set amount
- An electrically operated vacuum draws the bulk pellets or slats from the container through the wand and connecting hose to the melt tank for automatic replenishment

Pro-Fill System Specifications

- Adhesive Size: Pellets or slats up to .5-inches
- Adhesive Transfer Rate: Up to 750 lbs. per hour
- Operating Voltage: 120v or 220v
- Operating Air: Up to 80psi
- Connecting Hose & Vacuum Wand: Lengths up to 20 feet



**Hot Melt
Technologies, Inc.**
No One Puts It Together Like HMT.®

1723 W. Hamlin Road • Rochester Hills, Michigan 48309
Phone: 248-853-2011 | Fax: 248-853-6650
Email: info@hotmelt-tech.com
ISO 9001 – INTERNATIONAL QUALITY ASSURANCE STANDARD

©2015 Hot Melt Technologies, Inc. 3/15

hotmelt-tech.com