

It's Time To Step Up To A Benchmark® 215-HV.

Should you choose a hot melt system with a small melt tank – or a large one? A low-cost, low-volume unit ... or a higher-volume system that can accommodate future growth?

The 4th generation Benchmark 215-HV System from Hot Melt Technologies (HMT®,) simplifies your decision-making process. With its larger tank, high-output pump, and one or two-gun capacity, it's ready to work for you now ... and in the future.

Offering an excellent performance-to-price ratio, the Benchmark 215-HV is:

Pre-Assembled And Easy To Set-up

Plug the Benchmark 215-HV in to a 120-volt outlet, load it with adhesive and turn on the power. In just 30 minutes you're ready to start gluing.

Built Tough For Years Of Dependability

The Benchmark 215-HV includes a sealed, fractional-HP drive motor and cast aluminum melt tank. It also features a "cool touch" fiberglass shroud and high-strength hoses along with a gun (or guns) with steel nozzles.

Now With Front Panel Digital Temperature Control.

Simply adjust the temperature between 225°F and 400°F with the front panel readout, lock the setting, and keep meddling fingers away! The system monitors temperature to assure safe and trouble free operation.



Hot Melt Technologies, Inc.
No One Puts It Together Like HMT®.

Benchmark® 215-HV
Hot Melt System

Benchmark[®] 215-HV Hot Melt System

An Affordable Hot Melt System With
The Power To Meet Your Needs.

Benchmark 215-HV

The Benchmark[®] 215-HV Hot Melt System is perfect for medium- to high- volume product assembly and packaging applications. And, given HMT's reputation for quality, durability and performance, it's a system you can install with confidence.



SPECIFICATIONS

Tank Capacity

- 1.85 Gallons. (7 Liters)
Approx. 13 lbs.*

Number of Hoses/Guns

- 2 hoses/handguns

Hose Lengths

- 8, 12 or 16 feet

Handgun Configuration

- Standard Entry
- Top Entry
- In-Line Entry

Electrical

- 120 vac, 20 amp

Drive Motor

- All-electric, fractional HP

Pump

- Cast iron with steel gears

Viscosity

- Up to 10,000 cps

Flow Control

- Up to 50 lbs. per hour*

Melt Rate

- Up to 12 lbs. per hour*

Temperature Control

- Micro Processor
- From 225° F to 400° F

Dimensions

- 11" x 24" x 20" high (approx. 60 lbs.)

Warranty

- One-yr. limited warranty

Accessories

- Overhead Hose Boom & Balancer
- Steel Cart With Castors
- Shot Timer & Foot Switch
- Automatic Guns
- Guns Nozzles: Bead or Spray, interchangeable

Applications

- Case and carton sealing
- Woodworking
- Foam laminating
- Product assembly

* Rates will vary depending on adhesive type and viscosity.



Rely On HMT For All Your Hot Melt Application Needs.

Since 1981, Hot Melt Technologies has focused on making the best hot melt equipment available and sharing our application expertise with companies just like yours. At HMT, we know the importance of the products you manufacture. Our equipment - and your satisfaction with it are equally important to us. Everything we provide - from melt tanks to hoses, to guns and nozzles, to spare parts and accessories - is manufactured to the highest engineering, technical, and quality standards. From basic out-of-the-box applicators to specially designed systems, you can rely on HMT to remain committed to you and your continued satisfaction.

So, if you're seeking expertise, value, convenience and satisfaction, remember ...

No One Puts It Together Like HMT.



**Hot Melt
Technologies, Inc.**

No One Puts It Together Like HMT.

1723 West Hamlin Road • P. O. Box 80067 • Rochester, Michigan 48308
Tel: 248-853-2011 • Fax: 248-853-6650 • Web: www.hotmelt-tech.com
ISO 9001 - INTERNATIONAL QUALITY ASSURANCE STANDARD

©2015 Hot Melt Technologies, Inc. 1/15